



SECTION A-A

Notes:

1. Pitch: 7.62mm Poles:2-12p
2. Rated voltage/current:UL 300V/15A
VDE 400V/20A
3. Insulation resistance: 5000MΩ/1000V
4. Withstanding voltage: AC1500V/1Min
5. Wire range: 28-12AWG 2.5mm²
6. Temp. Range: -40° C~+105° C
7. Torque: 4.08kgf.cm(3.61lb.in)
8. Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to	over	to	over	to	over	to	over	
6	10	10	24	30	60	100	150	∩
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	□

5	2EDG Clamp	1005B00010 (H)	XX	Phosor bronze	Ni plated
4	DG128 Brass cage	X000000020 (H)	XX	Brass	Ni plated
3	2EDG "-" Screws-M2.5	S000001370 (H)	XX	Steel	Cr ³⁺ Zn
2	2EDGK-7.62-Cover	1006C0YXXA (H)	1	PA66	UL94V-0

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△		Drawing emend	WF	12/31/05
△		修改图面	CSX	05/04/07
△		增加VDE、CE认证标志	LJH	01/14/08

1	2EDGK-7.62-Housing	1006A0YXXA (H)	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
TOLERANCES EXCEPT AS NOTED		DFTO DZJ	DATE 09/26/05"		
MM (INCH)		CHKD	DATE		
.00 ±		MFO	DATE		
.000 ±		APPVL	DATE		
MATERIAL :		DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD			
ANGLES ± 1'		G.E :		NAME 2EDGK-7.62-XXP-1Y-00A(H)	
FINISH :		DRAWING NO. 2EDGK-7.62-E05		SIZE	REV
THIRD ANGLE PROJECTION		/PART NO.		A3	T3
SCALE : 1:1		DO NOT SCALE DRAWING		SHEET 1	OF 1