



TDA2822

LINEAR INTEGRATED CIRCUIT


DUAL LOW VOLTAGE POWER AMPLIFIER

■ DESCRIPTION

The UTC **TDA2822** is a monolithic integrated audio amplifier in a 8-Pin plastic dual in line package. It is designed for portable cassette players and radios.

■ FEATURES

- * Wide Operating Supply Voltage: $V_{CC}=1.8V - 12V$.
- * Low Crossover Distortion.
- * Low Quiescent Circuit Current.
- * Bridge/Stereo Configuration.




■ ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
TDA2822L-S08-R	TDA2822G-S08-R	SOP-8	Tape Reel
TDA2822L-S08-T	TDA2822G-S08-T	SOP-8	Tube
TDA2822L-D08-T	TDA2822G-D08-T	DIP-8	Tube

TDA2822L-D08-T (1) Packing Type (2) Package Type (3) Lead Free	(1) R: Tape Reel, T: Tube (2) D08: DIP-8, S08: SOP-8 (3) G: Halogen Free, L: Lead Free
--	---

■ PIN CONFIGURATIONS



■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	15	V
Output Peak Current	$I_{O(PEAK)}$	1	A
Power Dissipation	DIP-8	P_D	W
	SOP-8		
Operating Temperature	T_{OPR}	-20~+85	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-40~+150	$^{\circ}\text{C}$

Note:1. Absolute maximum ratings are stress ratings only and functional device operation is not implied. The device could be damaged beyond Absolute maximum ratings.


2. The device is guaranteed to meet performance specifications within $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ operating temperature range and assured by design from $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$

■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, $V_{CC}=6\text{V}$, $f=1\text{kHz}$, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Operating Supply Voltage	V_{CC}		1.8		12	V
Quiescent Circuit Current	I_{CC}	$V_{IN}=0$		9		mA
Closed Loop Voltage Gain	Stereo	G_{VC}		40		dB
	Bridge			40		
Channel Balance	CB	Stereo	-1	0	1	dB
Output Power(Stereo)	DIP-8	P_{OUT}	$V_{CC}=6\text{V}, R_L=4\Omega, \text{THD}=10\%$	0.4	0.65	W
	SOP-8			0.28	0.45	
	DIP-8		$V_{CC}=3\text{V}, R_L=4\Omega, \text{THD}=10\%$		0.11	W
	SOP-8				0.07	
Output Power (Bridge)	DIP-8	P_{OUT}	$V_{CC}=6\text{V}, R_L=4\Omega, \text{THD}=10\%$	0.9	1.35	W
	SOP-8			0.63	0.94	
	DIP-8		$V_{CC}=3\text{V}, R_L=4\Omega, \text{THD}=10\%$		0.35	W
	SOP-8				0.24	
Total Harmonic Distortion	Stereo	THD	$R_L=8\Omega, P_{OUT}=0.2\text{W}$	0.5		%
	Bridge		$R_L=8\Omega, P_{OUT}=0.5\text{W}$	0.5		%
Ripple Rejection	RR	Stereo, $f=100\text{Hz}, C_3=100\mu\text{F}$	24	30		dB
Output Noise Voltage	eN	Stereo, BW(-3dB)=20Hz ~20kHz		0.5	2.0	mV
Cross Talk	C_T	Stereo, $f=1\text{kHz}$		50		dB
Input Resistance	R_{IN}		100			k Ω

■ TEST CIRCUIT


STEREO





BRIDGE



■ SCHEMATIC DIAGRAM



■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.