



FEATURES


- High Power Density
- Over 500,000 cycle life (semi-permanent)
- 2 units serially connected to provide 6.0V products
- RoHS compliant
- Long-term reliability improved at high temperature and humidity




Drawing



I TYPE



O TYPE



H TYPE

D = 10.5mm

TYPE	I	O	H
P	5.5	15.5	10.5

(Unit : mm)

SPECIFICATION

ITEM		CHARACTERISTICS					
Product series		EDLC 2 SERIAL MODULE					
Rated Voltage (V _R)		6.0V					
Operating Temperature		-40 ~ +65°C					
Capacitance Tolerance		-10 ~ +30%					
High Temperature Load Life		After 1,000 hours at V _R loaded under +65°C, capacitors meet the following criteria.					
		Capacitance Change					≤ 30% of initial value
		ESR					≤ 2 times of specified value
Cycle Life Characteristics	Cycle	Over 500,000					
	ΔC	≤ 30% of initial value					
	ESR	≤ 2 times of specified value					
	Method	Cycle of Charge/discharge from V _R to 1/2V _R					
Shelf Life		2 Years					
		No Electrical Charge, Temperature below 70°C (ΔC : ≤ 10% of initial value / ΔESR : ≤ 50% of specified value)					
Part Number	Rated Voltage (V)	Capacitance (F)	ESR (mΩ)		Max. Current (A)	Leakage Current (mA, 72hr)	Size (mm) D x W x L
			AC(1kHz)	DC			
WEC6R0505QG	6.0	5.0	75	115	9.5	0.030	10.5x21x32

* Max. Current : 1 sec. discharge to 1/2V_R

* When do module more than 2 series, please fully discharge over 1 hour first, then assemble right after within 1 hour.