

P6AU-xxxxELF



PMA-SERIES

Rev.11-2008

- ✓ 1 Watt
- ✓ Unregulated
- ✓ **Single** Output
- ✓ **SIP4** Case
- ✓ **1 kV** DC I/O Isolation
- ✓ Low Ripple and Noise

The PMA series P6AU-xxxxELF is a family of cost effective 1 W single output DC/DC converters. These converters are in an ultra miniature SIP4 case. Devices are encapsulated. High performance features: 1000VDC input/output isolation, high efficiency operation, output voltage accuracy of $\pm 3\%$ maximum, input range of $\pm 10\%$ tolerance and low output ripple and noise.

All specifications typical at $T_a=25^\circ\text{C}$, nominal input voltage and full load unless otherwise specified

Input Specifications

Voltage Range	$\pm 10\%$
Input Filter	Capacitors
Input Reflected Ripple Current ¹	20 mA pk-pk

Output Specifications

Voltage Accuracy	$\pm 3\%$
Short Circuit Protection	Short Term
Line Regulation	$\pm 1.2\% / 1\% V_{in}$ Change
Load Regulation (20% - 100%)	$\pm 10\%$ (3.3V _{out} Models: $\pm 20\%$)
Ripple and Noise (20Mhz bandwidth)	100 mV pk-pk
Temperature Coefficient	$\pm 0.02\% / ^\circ\text{C}$

General Specifications

Efficiency	See Table
I/O Isolation Voltage (3 sec.)	1000 VDC
I/O Isolation Capacity	60 pF, typ.
I/O Isolation Resistance	1000 MOhm
Switching Frequency	80 kHz (Variable)
Humidity	95% rel H
Reliability Calculated MTBF (MIL-HDBK-217F)	> 1.121 Mhrs

Physical Specifications

Case Material	Non Conductive Black Plastic (UL94V-0 rated)
Potting Material	Epoxy (UL94V-0 rated)
Weight	~ 1.5g, typ.

Environment Specifications

Operating Temperature	-40 to +85 $^\circ\text{C}$ (ambient)
Maximum Case Temperature	100 $^\circ\text{C}$
Storage Temperature	-40 to +125 $^\circ\text{C}$
Cooling	Free Air Convection
RoHS Conform	Soldering 260 $^\circ\text{C}$, max. (1.5mm from case 10s.)

Selection Guide

Single Output

Order #	Input Voltage (VDC)	Input Current No Load (mA)	Input Current Full Load (mA)	Output Voltage (VDC)	Output Current Full Load (mA)	Efficiency (%)	Capacitor Load (uF) ²
SINGLE OUTPUT							
P6AU-3R33R3ELF	3.3	25	452	3.3	303	67	220
P6AU-3R305ELF	3.3	30	415	5	200	73	220
P6AU-053R3ELF	5	25	278	3.3	303	72	220
P6AU-0505ELF	5	25	267	5	200	75	220
P6AU-057R2ELF	5	25	264	7.2	138.8	76	220
P6AU-0509ELF	5	25	260	9	111.1	77	220
P6AU-0512ELF	5	25	257	12	83.3	78	220
P6AU-0515ELF	5	25	257	15	66.67	78	220
P6AU-0518ELF	5	25	257	18	55.5	78	220
P6AU-0524ELF	5	25	257	24	41.67	78	220
P6AU-123R3ELF	12	16	116	3.3	303	72	220
P6AU-1205ELF	12	16	112	5	200	75	220
P6AU-127R2ELF	12	16	110	7.2	138.8	76	220
P6AU-1209ELF	12	16	109	9	111.1	77	220
P6AU-1212ELF	12	16	107	12	83.3	78	220
P6AU-1215ELF	12	16	107	15	66.67	78	220
P6AU-1218ELF	12	16	107	18	55.5	78	220
P6AU-1224ELF	12	16	107	24	41.67	78	220
P6AU-243R3ELF	24	10	58	3.3	303	72	220
P6AU-2405ELF	24	10	56	5	200	75	220
P6AU-247R2ELF	24	10	55	7.2	138.8	76	220
P6AU-2409ELF	24	10	55	9	111.1	77	220
P6AU-2412ELF	24	10	54	12	83.3	78	220
P6AU-2415ELF	24	10	54	15	66.67	78	220
P6AU-2418ELF	24	10	54	18	55.5	78	220
P6AU-2424ELF	24	10	54	24	41.67	78	220
P6AU-483R3ELF	48	7	29	3.3	303	72	220
P6AU-4805ELF	48	7	28	5	200	75	220
P6AU-487R2ELF	48	7	27	7.2	138.8	76	220
P6AU-4809ELF	48	7	27	9	111.1	76	220
P6AU-4812ELF	48	7	27	12	83.3	76	220
P6AU-4815ELF	48	7	27	15	66.67	76	220
P6AU-4818ELF	48	7	27	18	55.5	76	220
P6AU-4824ELF	48	7	27	24	41.67	76	220

If you need other specifications, please enquire.

